

CNWU-61B

6,000 lumens, WUXGA DLP projector



Premium image quality

As the CNWU-61B displays crisp images with a high contrast - thanks to its high-quality lenses and optical design - it will turn your meeting room into a professional environment. Thanks to its standard WUXGA resolution, the projector supports any computer graphics or video centric content and will display a crystal clear image.

Increased efficiency

Whether your organization is a business, educational or governmental institution, investing in equipment that improves decision-making processes without compromising on ergonomics is important. The CNWU-61B provides razor-sharp, stable and high contrast images that don't tire your eyes and thanks to its low noise levels, working in an environment with front projection has never been more comfortable and productive. And as it comes in a compact and stylish design, it will perfectly match the interior of your meeting room.

Zero worries

The CNWU-61B has a filter-free design, an energy-efficient and flexible dual lamp system and uses the acknowledged DLP® technology for unmatched accuracy. Operating the projector in single lamp mode provides you with 5,000 worry-free hours of operation without component replacements. These factors allow you to reduce your installation and maintenance cost significantly.

BARCO

Visibly yours

Spécifications techniques

Type de projecteur	WUXGA, single chip DLP projector
Technologie	LVDC DMD™ with DarkChip3™
Résolution	1,920 x 1,200 (WUXGA)
Luminosité	6,000 lumens
Taux de contraste	6,500:1
Uniformité de la luminosité	>90%
Rapport d'aspect	16:10
Type de lentille	All pure glass lenses
Lentilles	0.79:1 EN12 ultra wide; 0.8-1.21:1 EN46 ultra wide zoom lens; 1.24-1.6:1 EN13 wide angle zoom lens; 1.6-2.32:1 EN11 standard zoom lens
Décalage de la lentille optique	Vertical: -134% to +134%; Horizontal: -68% to +68% (on zoom lenses)
Correction des couleurs	RealColor™
Lampes	2 x 300W UHP Vidi
Durée de vie de la lampe	Up to 2,000 hours (full power) / Up to 2,500 hours (eco mode)
Boîtier de lampe, remplacement rapide	Yes
Garantie de la lampe (remplacement site/remplacement usine)	sur 500 hours or 90 days
Cœur de processeur DLP™ scellé	Yes
Orientation	table - ceiling
serveur web intégré	Yes
3D	Passive polarized and Infitec (2 projectors)
Entrées	1 x DVI-D; 1 x HDMI 1.3a; 1 x VGA; 1 x 5-BNC; 1 x HDMI 1.3a; 1x YPbPr; 1 x S-video; 1 x composite
Résolutions en entrée	1,920 x 1,200 - 640 x 480 pixel resolution; RGBHV, RGBS, RGSB; custom formats available; HDTV (1080p, 1080i, 720p); NTSC, PAL, SECAM
Horloge pixel max.	165 MHz
Outils logiciels	Projector Toolset, ProNet
Contrôle	Minijack + IR, RS232, Network, 12v trigger
Connexion réseau	10/100 base-T, RJ-45 connection
Alimentation électrique	100-240V / 50-60Hz
Consommation maximale	850W
Niveau sonore (habituel à 25 °C/77 °F)	41.9dB (ISO 9296)
Température ambiante de fonctionnement	10-40°C / 50°-104°F
Humidité (fonctionnement)	20-80% RH
Dissipation BTU	max 2,900 BTU/h
Dimensions (l x L x H)	510 x 233 x 376 mm / 20.08 x 9.17 x 14.80 inches
Poids	12.6 kg (27.8 lbs)
Shipping dimensions (WxLxH)	520 x 370 x 780 mm / 20.47 x 14.57 x 30.71 inches
Poids à l'expédition au départ de l'usine	20 kg (44 lbs)
Accessoires standard	Power cord, wireless remote control
Certifications	Compliant with FCC, part 15 Class A and CCC, cCSAus, cUL, UL and CE
Garantie	Limited 3 years parts and labor.
X-port™	No

Crée le : 05 août 2013
 Les spécifications techniques sont susceptibles d'être modifiées sans préavis.
 Veuillez consulter les dernières informations disponibles sur www.barco.com.

BARCO

Visibly yours